

CODE: MBK22-FFECO-6

ERP: 0501142

Fire Extinguisher 6 L with Ecological Fluorine Free Foam Fluorine Free

Fire Extinguisher 6 L water with additive, with one seam vessel, Internal Plastic Layer and Safety Release Valve. 100% PFAS FREE
METALLIC BRACKET INCLUDED [FIRE EXTINGUISHERS USER INSTRUCTIONS](#)



CHARACTERISTICS

Approval Type	BENOR, BSI, GTC, MED, NCP - KIWA, VKF
Extinguisher Type	Portable
Pressure Type	Stored Pressure
Suppression Agent Type	Fluor Free, Water
Capacity	6 L
Extinguishing Agent	Water with additive
Operating Temperature	+5 to +60 °C
Max Allowable Pressure	18 bar
Test Pressure	27 bar
Volume of Equipment	7,9 L
Cylinder Height	470±5 mm
Cylinder Diameter	160±1,5 mm
Cylinder Neck Thread	M30x1,5
Cylinder Material	DC01 (St12)
Valve Material	HPb59-1 (Nikel Plated)
Safety Valve	19-26 bar
Approx. gross Weight	10,5 kg
Approx. Dimensions	630x200 mm
Paint Finish	RAL 3000



Issue Date: 17/04/2025

Information may change

HEADQUARTERS: KATHIANA AKROTIRIOU P.C. 73100 CHANIA, CRETE - GREECE, TEL.: +30 28210 63222, FAX :+30 28210 91644

ATHENS DISTRIBUTION CENTER: SHINEZA - ASPROPIRGOS, P.C. 19300, ATTICA - GREECE, TEL.: +30 210 4614006, FAX: +30 210 5595986

NORTH GREECE DISTRIBUTION CENTER: 8 ARKADIOU str. KALOCHORI - THESSALONIKI, P.C. 57009, TEL.: +30 2310 785668, FAX: +30 2310 574793

CENTRAL & EAST CRETE DISTRIBUTION CENTER: P' str. INDUSTRIAL ZONE OF HERAKLION - CRETE - GREECE, P.C. 71601, TEL/ FAX: +30 2810 333151

www.mobiakfire.com